

I'm not a robot!

11788196.888889 20621004.478261 16685007.113402 202693595810 85275189.833333 54551303.95 1156353160 7157494.4148936 76505590.117647 105253798896 31111022.955556 76767667808 215901133.5 47169843.190476 13157279.12 16277430468 107714247.90909



Baofeng uv-9r plus user manual. Manual baofeng uv-9r plus. Baofeng uv-9r plus manual programming.

Press the button [^] or [I] to select the desired parameter. 6 - BATERIAL CARREGER: Use only the charger specified by the manufacturer. Example: If we want to maintain communication It is through a repeater whose input frequency is 145,000 MHz and 145,600 MHz healthy, we have to select the "offset" in 0600 and the "SHIFT" direction negative displacement (-) and the transmitter-receptor will receive the repeater's health frequency 145,600 MHz and when [PTT] automatically issue the repeater input frequency 145 000 MHz 12,15 à STE (ELIMINATION OF TOM COLA): This option It is used to remove the sound of the carrier after the transmission is completed. "BOTH": The "ID": It is transmitted when you press or release [PTT]. List of rhinestone program and not CTCSS standards. 30Voltage up to 21/07/2022R\$3 discountCode:A HORI13515 Gasto MAn. In extremely cold conditions Replacement battery is required. • Battery on high capacity site. Never obstruct the charging cycle or remove the battery when it is charged. Connect the AC adapter to the socket. Dust in battery contacts can cause for work or charging. [VFO / MR]: Press the [VFO / MR] key to change the channel mode frequency mode. Repeat this procedure to CAD 6 months. Often you have defined. Temperatures outside this range can cause leakage or damage. àÁ à Adjustable SQUELCH à Adjustable from 0 to 9. 5.3 à MICROFONE INSTALLATION AND EXTERNAL OUVID FONE: Connect the earphone and external microphone connector at the input of àSP. Note: -Consult the vendor or reseller to get information Options on available options. • Display lighting and programmable keyboard. • FM radio receiver (65 MHz to 108MHz). 8Limited to: 5Video up to 2022R\$2 discountCode:A HORI1325Gasto MAn. 7 à INFORMATION ON BATERIA New batteries loaded completely. 12.3 à FUNION àVOXà (VOZ TREATMENT): This function is not necessary to press the [PTT] key to transmit. 12.6 - TOT (TRANSMISSION TIME CONTROLE): With this option, you can automatically control the time you can transmit every time you press the [PTT] key, where this option It is very good for conversations not too extensive and preserve final transistors of the unit. It is recommended to place it on Level 5. With the "silencer" level correctly set, you listen only when you receive signals and significantly reduce battery consumption. While Radio FM in the press [SCAN] to look for stadium stations. For more information, see your dealer or representative. Press and hold [MONII] to control the signal. To avoid the risk of injuries, do not throw the battery on fire. In the transmission mode, press the numeric code keyboard to send signals (the code must be inserted by the PC software). 10 - 1750 Hz TOM TO ACESS REPETITORS: User can set up long distance communication through amateur radio repeater is activated after receiving a tone Press 1750 Hz and hold the [PTT] key and press [BAND] to transmit a 1750 Hz. 11 tone Basic OPERATIONS: Check that the antenna and battery are properly installed. 7.4 - BATERIAL AREA 1. [#]: In the channel in any area where affixed warning instructs you to do so. When charging a battery installed in the stadium, turn it onenoserP .rotpecsnart sues soa sonad rative arap .sonem u.1.5.1 acrec. @ ÁRVWSâ o euq es-adrcnac. anrexte anetna amu rasu @Ácov eS-. árodaicneisâ o parepus arap etneicifus o etrot. @ Álanis es adahcef @ Áoid@Ar ed rossimam o edepmi @OLCB@ acits@retcarac amU):ODAPUCO LANAC ED OIEUQOLB(LCB à 21.21 .rodagerrac od si@Art ed etrap an rodatpada o euqL .rolac ed etnof ed ol;@acoloc men .opnet ognol mu etnarud ateral ralos zu. @ oid@Ar o ainc@Arrocnoc x@FAN @ Álanis lanas od oF@Áa@arud a u arbif an ecenamrep e lanis mu atected odnaug arap oF@Áa@azlatigD):ardatropsnart anmu ed s@Avarta oF@Áa@repO @OC@ .ragilis arap ramoter . 3 .oid@Ar od oproc od roirefini etrap ad oxabia 2 a 1 ed acrec ed @ Áiretab ad roirefini etrap A .orb ed issach a m@atoc mob me e olarap me @ Áise airtab a es air@Assecan airtab a racolos odnauQ - AIRETAB AD SEÁALATSNI à 4.5 .megabahme ed laiream o retraces ed setna riuges a sodatsil so equifitned @Ácov euq adhemocer .CP ed erawftos olep sanepa odinmed reS .sodiet sues ed egno l sorteme@tne 4 a 3 enforcum o moc lacitrev oF@Áslop an oid@Ar o eruges .lit@Atrap oid@Ar mu moc ritmssnat oF@Ás .roiretsop osu arap meb o-n@Átnam .etneibma arutarepmet ad oxiba rahlabart edop oF@Ásautis atses rahlabart ed zapaci .arf airtab A .sorteme@rap ed oF@Ás@udortni a raeheg arap etnemavon .ethemlaudarg B e A ertna arepo etnemarar euq etimrep orserucr etsE)@ÁAPECR LAUD / LAUD NETSIL(RDT à 5.21 .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o etnarud marof uo odnataf reviste meti mugla eS .nnm otsG45651ROH A-ogid3ACF0 %03.sarmroc ed ohmrae ues ed sotdorpsoa soj@L ad snapoC so odnatzilu siam ezimonocEajol ad snopuCdnaB lau@FHU/FHV adazilautaW51 sulP R9-VU GNEPOAB eikla T elkl@W oidaR rey@P hs@F daolnwod oediv sihew@P rolo@elbaliava ton egam@ .odatceted alcnaAuqerf ed lanis odnaug me ecenamrep and rarucor Q :acsu@ed o'repo@ES\opmil rias uo ralecnac a P :rjas@ .loP 2.3 k@t yaW-2 aremc@C etneibma zuL sair@Af ed ratnaj ra@VTK otmemanezamrA ed asl@ob otmen elortoc moc soelc@Án a ofot ad arutarepmet onrebs oedAV lit@Atrap odiroloc of@tsab ed zul BGR otmemhne ed zuL ederap ed lepap ed zuL ajoL ad aniq@Ap reV rb.1scinortcele_nozirohajol ad snopuC2202/7/12 @Ata odil@AV005 .atelpmo agrac amu for the game On the other hand, this transmission tool is switched on. 12.11 - PTT - ID (PRESSED OR SOLTA THE PTT BOTON FOR TRANSMITTING SINAL CODIFICATION): This feature allows you to identify the person you announced. The transceiver switched off automatically when the game time. 12.8 - ANI (ANI) is also known as "PTT - ID", since it transmits an "ID" identification. Each time you load or the [PTT] transmission button. Use a clean dry cloth to try to connect the battery to the radio. "OFF": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Not modified the radio for any reason. The "SQUELCH" only opens when a coded tool "CTCSS" or "DCS" the same that was programmed on the emitter device. 8.2 - DEFINITION OF TECLAS AND COMANDOS (PTT): tests and hold [PTT] to transmit, release to receive. In the charger there is an LED indicated recharge progress. 5Limited to: 2 Valid until 07/03/202260% OFFICE: HORI94854 Mu gas .Do not hold the antenna with your hand or wrap outside to prevent malfunction of the transceiver. "DT - ANI": When you are transmitting do not hear the tone of "DTMF". 5.3. Note: The following menu options are invalid channel mode: CTCSS, DCS, W/N, PTT - ID, BCL, AD SCAN TO, S - NOME channel code. • Turn off the radio before boarding a plane. • No.me ertne ,rovaf rop .etropsnart o